IPC-52B4AP-FMU

2MP Fixed Bullet Network Camera




Based on Briton's advanced technologies, Value Series provides intelligent, simple and inclusive products and solutions. The system focuses on human targets, vastly improving alarm efficiency and effectiveness.



Key Features

- High quality imaging with 2MP resolution
- Efficient H.265 compression technology
- Focus on human targets classification
- Water and dust resistant (IP67)
- Built-in microphone for real-time audio security

Dimensions



داتیس
ضمانت خرید شماست

Specification

Camera	
Image Sensor	1/3" Progressive Scan CMOS Sensor
Min. Illumination	Color: 0.01 Lux (F2.0, AGC ON) , 0 Lux with light
Illumination Distance	30 m (IR light) 30 m (warm light)
Smart IR	Support
Pan/Tilt/Rotation Range	Pan: 0° ~ 360° Tilt: 0° ~ 85° Rotation: 0° ~ 360°
Lens	
Focal Length	2.8, 3.6 mm
Aperture	F2.0
FOV	2.8mm@F2.0 Horizontal FOV: 98°, Vertical FOV: 55°, Diagonal FOV: 114° 3.6mm@F2.0 Horizontal FOV: 78°, Vertical FOV: 41°, Diagonal FOV: 92°
Lens Mount	M12
Compression Standard	
Video Compression	H.264/H.265
H.264 Codec Profile	Base/Main/High profile
H.265 Codec Profile	Main profile
Video Bit Rate	11 Kbps ~ 8Mbps
Triple Streams	N/A
Audio Compression	G.711A/G.711U
Audio Bit Rate	64 Kbps
Image	
Max. Image Resolution	1920 × 1080
Main Stream	50Hz: 25fps 1080P (1920 × 1080) 25fps 960P (1280 × 960) , 25fps 720P (1280 × 720) 60Hz: 30fps 1080P (1920 × 1080) 30fps 960P (1280 × 960), 30fps 720P (1280 × 720)
Sub Stream	50Hz: 25fps D1 (704 × 576) , 25fps CIF (352 × 288) 60Hz: 30fps D1 (704 × 480) ,30fps CIF (352 × 240)
Third Stream	N/A
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
Shutter Time	Auto/Manual, 1/3 ~ 1/100000s


داتیس
ضمانت خرید شماست

Day/Night	IR Cut Filter
Wide Dynamic Range	DWDR
Digital Noise Reduction	2D/3D DNR
BLC	Support
HLC	Support
ROI	Support
Rotate	N/A
Smart Feature	
Basic Event	Motion detection, video tampering
Smart Event	Smart motion detection, line crossing, area Intrusion (support alarm triggering by specified target types (human and vehicle))
Face Detection	N/A
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P
System Compatibility	Onvif (Profile G, Profile S, Profile T) , CGI
Security	User authentication, IP address filtering, Video mask
User	Up to 10 user
Web Browsers	Plug-in required live view: IE 10, IE 11 Local service: Chrome 57.0+, Firefox 52.0+
Mobile Surveillance	iPhone, iPad, Android devices
Interface	
Communication Interface	1 RJ45 10M / 100M Ethernet Port
On-board Storage	Up to 256G
MIC	Support
Speaker	N/A
Audio I/O	N/A
Alarm I/O	N/A
Reset Button	N/A
General	
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE	PoE (802.3 af)
Power Consumption	MAX.4.5 W

داتیس
ضمانت خرید شماست

Protection Level	IP67
Material	Graphene
Dimensions	Φ 70.6 × 160.7 mm (Φ 2.78" × 6.33")
Gross Weight	285 g (0.63 lb)

Related Accessories

LB10	LB01B	LB02	PM03
Junction Box,Φ112.5 × 49.5 MM	Junction Box, 145.2 × 145.2 × 53.5 MM	Junction Box,non-waterproof , Φ103.3 × 37.8MM	Pole Mount , Φ170 × 135.8 ×43.7 MM
			

Please select accessories according to the installation scenario:

